

Industrial Ethernet Switch - FL SWITCH SFNT 8TX - 2891005

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Wide-temperature Ethernet switch, 8 TP RJ45 ports, automatic detection of data transmission speed of 10/100 Mbps (RJ45), autocrossing function, reads QoS priority messages, accepts security frames

Your advantages

- ✓ Auto negotiation and autocrossing detection simplifies installation and setup
- ✓ Alarm contact for power supply and link status diagnostics
- ✓ Local diagnostic indicators with LEDs
- ✓ The switch also offers cable locking and port blocking
- ✓ QoS-prioritized (Quality of Service) messages
- ✓ Wide operating temperature range (-40°C ... +75°C)
- ✓ RJ45 ports support a transmission speed of 10/100 Mbps; fiber optic ports support 100 Mbps



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| GTIN |  4 046356 457200 |
| GTIN | 4046356457200 |
| Weight per Piece (excluding packing) | 460.000 g |
| Custom tariff number | 85176200 |
| Country of origin | Taiwan |

Technical data

Note

| | |
|-------------------------|---|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---|

Dimensions

| | |
|--------|--------|
| Width | 50 mm |
| Height | 130 mm |
| Depth | 100 mm |

Industrial Ethernet Switch - FL SWITCH SFNT 8TX - 2891005

Technical data

Ambient conditions

| | |
|--|--|
| Degree of protection | IP20 |
| Ambient temperature (operation) | -40 °C ... 75 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |
| Permissible humidity (operation) | 5 % ... 95 % (non-condensing) |
| Permissible humidity (storage/transport) | 5 % ... 95 % (non-condensing) |
| Air pressure (operation) | 62 kPa ... 108 kPa (up to 4160 m above mean sea level) |
| Air pressure (storage/transport) | 62 kPa ... 108 kPa (up to 4160 m above mean sea level) |

Interfaces

| | |
|-------------------------------|-----------------------------------|
| Interface | Ethernet (RJ45) |
| No. of ports | 8 (RJ45 ports) |
| Note on the connection method | Auto negotiation and autocrossing |
| Transmission physics | Ethernet in RJ45 twisted pair |
| Transmission speed | 10/100 Mbps |

Function

| | |
|----------------------------------|--|
| Basic functions | Unmanaged switch / autonegotiation, complies with IEEE 802.3, store and forward switching mode, includes QoS and alarm contact |
| Additional functions | Autonegotiation |
| Status and diagnostic indicators | LEDs: U _{S1} , U _{S2} (redundant voltage supply), link and activity per port |

Network expansion parameters

| | |
|---|--|
| Cascading depth | Network, linear, and star structure: any |
| Maximum conductor length (twisted pair) | 100 m |

Supply voltage

| | |
|-----------------------------|--|
| Supply voltage | 24 V DC (redundant) |
| Residual ripple | 3.6 V _{PP} (within the permitted voltage range) |
| Supply voltage range | 9 V DC ... 32 V DC |
| Typical current consumption | 155 mA (at U _S = 24 V DC) |
| Max. current consumption | 490 mA (@9 V DC) |

General

| | |
|------------------|--------------|
| Mounting type | DIN rail |
| Type AX | Block design |
| Net weight | 460 g |
| Housing material | Aluminum |

Standards and Regulations

| | |
|-------------------------------|--|
| Electromagnetic compatibility | Conformance with EMC Directive 2004/108/EC |
| Noise emission | EN 61000-6-4 |
| Noise immunity | EN 61000-6-2 |
| Conformance | CE-compliant |
| ATEX | # II 3 G Ex nA nC IIC T4 Gc |

Industrial Ethernet Switch - FL SWITCH SFNT 8TX - 2891005

Technical data

Standards and Regulations

| | |
|----------------|------------------------------------|
| IECEX | Ex nA nC IIC T4 Gc |
| UL, USA/Canada | Class I, Div. 2, Groups A, B, C, D |

Environmental Product Compliance

| | |
|------------|---|
| | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 10; |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 19170402 |
| eCl@ss 4.0 | 27250501 |
| eCl@ss 4.1 | 27250501 |
| eCl@ss 5.0 | 19030117 |
| eCl@ss 5.1 | 19030100 |
| eCl@ss 6.0 | 19170100 |
| eCl@ss 7.0 | 19170106 |
| eCl@ss 8.0 | 19170106 |
| eCl@ss 9.0 | 19170106 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000734 |
| ETIM 3.0 | EC000734 |
| ETIM 4.0 | EC000734 |
| ETIM 5.0 | EC000734 |
| ETIM 6.0 | EC000734 |
| ETIM 7.0 | EC000734 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 43172901 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11 | 43172015 |
| UNSPSC 12.01 | 43201410 |
| UNSPSC 13.2 | 43222612 |

Approvals

Approvals

Industrial Ethernet Switch - FL SWITCH SFNT 8TX - 2891005

Approvals

Approvals

BV / GL / LR / NK / GL-SW / ABS / BSH / UL Listed / cUL Listed / EAC / EAC / KC / GL / cULus Listed

Ex Approvals

IECEX / ATEX / UL Listed / cUL Listed / cULus Listed

Approval details

| | | | |
|------------|--|---|------------------|
| BV | | http://www.veristar.com/portal/veristarinfo/generalinfo/approved/approvedProducts/equipmentAndMaterials | 22935/B1 BV |
| GL | | https://approvalfinder.dnvgl.com/ | 86569-10 HH |
| LR | | http://www.lr.org/en | 10/20002 |
| NK | | http://www.classnk.or.jp/hp/en/ | TA15641M |
| GL-SW | | | 86569-10 HH |
| ABS | | http://www.eagle.org/eagleExternalPortalWEB/ | 14-HG1290743-PDA |
| BSH | | http://www.bsh.de/de/index.jsp | 627 |
| UL Listed | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 140324 |
| cUL Listed | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 140324 |
| EAC | | | EAC-Zulassung |

Industrial Ethernet Switch - FL SWITCH SFNT 8TX - 2891005

Approvals

| | | |
|-----|--|--------------------------|
| EAC | | RU *- DE.A*30.B.01735 |
|-----|--|--------------------------|

| | | | |
|----|--|---|--------------------------|
| KC | | http://eng.kcc.go.kr/user/ehpMain.do | KCC-REI- PCK-FL289100 |
|----|--|---|--------------------------|

| | | |
|----|--|--|
| GL | | |
|----|--|--|

| | | |
|--------------|--|--|
| cULus Listed | | |
|--------------|--|--|

Accessories

Accessories

Assembly adapter

Mounting plate - FL PA SFNT 5-8 - 2891012



Mounting plate for SFNT switches

End block

End clamp - E/NS 35 N - 0800886



End clamp, width: 9.5 mm, color: gray

Patch cable

Patch cable - FL CAT5 PATCH 0,3 - 2832250

Patch cable, CAT5, assembled, 0.3 m

Industrial Ethernet Switch - FL SWITCH SFNT 8TX - 2891005

Accessories

Patch cable - FL CAT5 PATCH 0,5 - 2832263

Patch cable, CAT5, assembled, 0.5 m

Patch cable - FL CAT5 PATCH 1,0 - 2832276

Patch cable, CAT5, assembled, 1 m

Patch cable - FL CAT5 PATCH 1,5 - 2832221

Patch cable, CAT5, assembled, 1.5 m

Patch cable - FL CAT5 PATCH 2,0 - 2832289

Patch cable, CAT5, assembled, 2 m

Patch cable - FL CAT5 PATCH 3,0 - 2832292

Patch cable, CAT5, assembled, 3 m

Patch cable - FL CAT5 PATCH 5,0 - 2832580

Patch cable, CAT5, assembled, 5 m

Patch cable - FL CAT5 PATCH 7,5 - 2832616

Patch cable, CAT5, assembled, 7.5 m

Patch cable - FL CAT5 PATCH 10,0 - 2832629

Patch cable, CAT5, assembled, 10 m

Protective cap

Industrial Ethernet Switch - FL SWITCH SFNT 8TX - 2891005

Accessories

Dust protection - FL RJ45 PROTECT CAP - 2832991



Dust protection caps for RJ45 socket

Safety locking

Port Guard Security Element - FL SEC PAC 4TX - 2832865



Layer1 security elements for four RJ45 network connections for use with patch boxes and panels
